

## **REGENCY ALTERRA®** | Ci1150 Small Non-Catalytic Wood Insert

This Alterra small contemporary cast iron wood insert provides a flush and clean design for your existing fireplace. This compact wood heater provides exceptional heating capacity and the two-speed blower helps distribute the heat to the far corners of your living space.

## **FEATURES**

- $\circ$   $\;$  Large fire viewing area, with heat radiating ceramic glass
- Cast iron faceplate provides additional radiant heating
- $\circ$   $\;$  Heavy duty cast hinges that will never bend or break  $\;$
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front mounted air adjustment
- $\circ$   $\;$  High performance brick-lined firebox reflects heat
- $\circ$   $\;$  Non-obtrusive air wash curtain keeps glass clean  $\;$
- $\circ$   $\,$  Heavy gauge steel log retainers to stop logs from rolling
- Reversible cast iron door with removable handle
- $\circ \quad {\sf Flush \ mount \ 2 \ speed \ blower}$

## **OPTIONS**

- Regular or custom made backing plates
- Standard or 4-1/2" offset flue adaptor
- Regency stainless steel flex liner kits
  (5.5" DIA) in 25 ft. and 35 ft. lengths
- Flue connectors
- Wrap insulation kits

## SPECIFICATIONS

Maximum BTU*	55,000
Typical sq. ft. heated**	600 - 1,200
Efficiency (EPA LHV)	75%
Max log size	18"
Burn time	Up to 8 hours
Emissions	1.7 g/h
Firebox size	1.3 cu. ft.
Flue size	6"

MIN. FIREPLACE OPENING		
Width (front) x Height	25" x 23"	
Depth (standard flue adapter)	15-1/16"	
Depth (offset flue adapter)	17-11/16"	

NOTE: The ember protection shown in these images may not accurately reflect the ember protection dimensions required for your area.

\* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation. Refer to page 18 for BTU calculation method.

\*\* Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.