



F2500 shown with pedestal base and black cast iron door and airmate.

### FEATURES

- EPA 2020 certified
- Front mounted air adjustment & catalytic bypass
- Air & bypass operating tool
- Easy to read catalytic thermometer
- High performance brick-lined firebox
- Clean glass airwash system
- Rear heat deflector
- Mobile home\*\* and alcove approved
- Closest clearances in the industry
- 10-year 100% coverage on original catalyst

\*\*Approved in USA only

### OPTIONS

- Cast iron door with ceramic glass in black or nickel accent
- Pedestal base
- Cast iron legs in black or brushed nickel
- Ash drawer
- 2 speed blower
- Convector airmate
- Outside air kit

### SPECIFICATIONS

Maximum BTU*	78,000
Typical sq. ft. heated**	1,000 - 2,200
Efficiency (EPA LHV)	81%
Max log size	18"
Burn time	Up to 12 hours
Emissions	1.0 g/h
Firebox size	2.3 cu. ft.
Flue size	6"

\* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

\*\* Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR  
100% ORIGINAL  
COMBUSTOR COVERAGE